

November 2014

# 1N4001 - 1N4007 General-Purpose Rectifiers

### **Features**

- Low Forward Voltage Drop
- · High Surge Current Capability



# **Ordering Information**

Part Number	Top Mark	Package	Packing Method
1N4001	1N4001	DO-204AL (DO-41)	Tape and Reel
1N4002	1N4002	DO-204AL (DO-41)	Tape and Reel
1N4003	1N4003	DO-204AL (DO-41)	Tape and Reel
1N4004	1N4004	DO-204AL (DO-41)	Tape and Reel
1N4005	1N4005	DO-204AL (DO-41)	Tape and Reel
1N4006	1N4006	DO-204AL (DO-41)	Tape and Reel
1N4007	1N4007	DO-204AL (DO-41)	Tape and Reel

## **Absolute Maximum Ratings**

Stresses exceeding the absolute maximum ratings may damage the device. The device may not function or be operable above the recommended operating conditions and stressing the parts to these levels is not recommended. In addition, extended exposure to stresses above the recommended operating conditions may affect device reliability. The absolute maximum ratings are stress ratings only. Values are at  $T_A = 25^{\circ}\text{C}$  unless otherwise noted.

	Parameter		Value						
Symbol			1N 4002	1N 4003	1N 4004	1N 4005	1N 4006	1N 4007	Unit
$V_{RRM}$	Peak Repetitive Reverse Voltage	Repetitive Reverse Voltage 50 100 200 400 600 800 1000		1000	V				
I <sub>F(AV)</sub>	Average Rectified Forward Current .375 " Lead Length at T <sub>A</sub> = 75°C		1.0						Α
I <sub>FSM</sub>	Non-Repetitive Peak Forward Surge Current 8.3 ms Single Half-Sine-Wave	3()		А					
l <sup>2</sup> t	Rating for Fusing (t < 8.3 ms)		3.7						A <sup>2</sup> sec
T <sub>STG</sub>	Storage Temperature Range		-55 to +175					°C	
TJ	Operating Junction Temperature		-55 to +175					°C	

# **Thermal Characteristics**

Values are at  $T_A = 25$ °C unless otherwise noted.


Symbol	Parameter	Value	Unit
$P_{D}$	Power Dissipation	3.0	W
$R_{\theta JA}$	Thermal Resistance, Junction-to-Ambient	50	°C/W

## **Electrical Characteristics**


Values are at  $T_A = 25$ °C unless otherwise noted.

Symbol	Parameter	Conditions	Value	Unit
V <sub>F</sub>	Forward Voltage	I <sub>F</sub> = 1.0 A	1.1	V
I <sub>rr</sub>	Maximum Full Load Reverse Current, Full Cycle	T <sub>A</sub> = 75°C	30	μΑ
1.	Reverse Current at Rated V <sub>R</sub>	T <sub>A</sub> = 25°C	5.0	μA
IR	Reverse Current at Nateu V <sub>R</sub>	T <sub>A</sub> = 100°C	50	μΑ
C <sub>T</sub>	Total Capacitance	$V_R = 4.0 \text{ V}, f = 1.0 \text{ MHz}$	15	pF

# **Typical Performance Characteristics**



**Figure 1. Forward Current Derating Curve** 



20

Figure 2. Forward Characteristics






Figure 3. Non-Repetitive Surge Current



**Figure 4. Reverse Characteristics** 

Ú¢WWXÓÜ				
ÞÓÜ	ÖÒÙÔÜŒVŒÞ	ÖŒ/Ò	ÓŸĐŒÚÚ©	
F	ÜÒŠÒŒÙÒÖÁ/UÁÖÔÔ	GJRWŠ€Ì	PŸŒÞÕÐÁÛWZPUW	
G	ÔPCEÞŐÒÁ KESEÁUÁ KEFÈ ÔPCEÞŐÒÁÞUVÒÁÓÁKKEÖÖÖÖÁÚŠCEÚVÔGÓUÖŸÈ ŰÖTUXÓÁŐŠCEJUÁÚÞÁVQSŐÉ	FJÙÒÚ€Ì	PŸŒÞÕÐÂÛWZPUW	



ÞU V Ò Ù KÁN Þ Š Ò Ù Ú ÁU V P Ò Ü Y QÙ Ó ÁU Ú Ò Ô Q Q Ò Ö

AMOEMÁJOEÔS CEÕ ÒÁJVOEÞÖCE JÖÁJ ÒZOÒU ÒÞÔÒKÁ
RÒÖOÔÁÖU EÐEL ÁK CEJ QEVQU ÞÁQEŠÈ
AMÓDÁJOEÔS CEÑ ÒÁÓU ÖŸ ÁÔCEÞÁÓ ÁJ ŠCEÙ VQĎÁJ Ü ÁK
AMMIMIR ÒÜT ÒV QÔCEŠŠÝ ÁJ ÒCEŠOÖ ÁŐ ŠCEÙ ÚÆ:
AMÖDÁGEŠÁÖGT ÒÞ ÙQU Þ ÙÁQEJ ÒÁQÞÁT (SŠST ÒV ÒÜ ÙÈ
AMÖDÁGEŠÝÖGT QÞÔÁZSŠÒÁÞ CET ÒKÖU I FOEÜ ÒX G

ŒÚÚÜUXŒŠÙ	ÓÆOÖ			
ÖÜGY ÞK ÓUÓUŸÁT ŒŠÖU	FJÙÒÚ€Ì	FAIRCHILD		
<sup>ôpòôsòōK</sup> PÒÞÜŸÆŸŒ₽Õ		SEMICONDUCTOR™		
œúûUxòōK ÓŸÁPWŒĐŐ		OEÝ ØJEŠÁŠÒCIEĎ ÖČIÉÁ		
ŒÚŰUXÒĞK PUY ŒÜÖÁŒŠŠÒÞ		RÒÖÒÔÁÖUGEIĒKOEÜQOE/QUÞÁQEŠ		
ÚÜURÒÓVQIÞ ŽTTá		iódesió vízeó ouder de olevir docu FIFF ÞEDE TSVEÖUIFŒ G		
Q ÔP		ØUÜT ÖÜŠŸK ÞÆDE ÙPÒÒVÁK FÁUØÁF		





#### TRADEMARKS

The following includes registered and unregistered trademarks and service marks, owned by Fairchild Semiconductor and/or its global subsidiaries, and is not intended to be an exhaustive list of all such trademarks.

AccuPower™ F-PFS™ FRFET® Awinda<sup>®</sup>

AX-CAP®\* Global Power Resource<sup>SM</sup>

BitSiC™ GreenBridge™ Build it Now™ Green FPS™ CorePLUS™ Green FPS™ e-Series™

CorePOWER™ Gmax™ CROSSVOLT™ GTO™  $CTL^{TM}$ IntelliMAX™

Current Transfer Logic™ ISOPLANAR™ **DEUXPEED®** Making Small Speakers Sound Louder

Dual Cool™ and Better™ EcoSPARK® MegaBuck™

EfficientMax™ MIČROCOUPLER™ ESBC™ MicroFET™ MicroPak™

MicroPak2™ Fairchild® MillerDrive™ Fairchild Semiconductor® MotionMax™ FACT Quiet Series™ MotionGrid® FACT® MTi<sup>®</sup> MTx®

MVN® mWSaver® FPS™ OptoHiT™ OPTOLOGIC®

\* Trademarks of System General Corporation, used under license by Fairchild Semiconductor.

OPTOPLANAR®

PowerTrench® PowerXS™

Programmable Active Droop™

**QFET** QS™ Quiet Series™ RapidConfigure™

Saving our world, 1mW/W/kW at a time™

SignalWise™ SmartMax™ SMART START™

Solutions for Your Success™

SPM® STEAL TH™ SuperFET® SuperSOT™-3 SuperSOT™-6 SuperSOT™-8 SupreMOS® SyncFET™ Sync-Lock™

SYSTEM SYSTEM

TinyBoost<sup>®</sup> TinyBuck<sup>®</sup> TinyCalc™ TinyLogic<sup>®</sup> TINYOPTO™ TinvPower™ TinyPWM™ TinyWire™ TranSiC™ TriFault Detect™

TRUECURRENT®\* uSerDes™

UHC'

Ultra FRFET™ UniFET™  $VCX^{TM}$ VisualMax™ VoltagePlus™ XSTM. Xsens™ 仙童™

#### DISCLAIMER

FastvCore™

FFTBench™

FAIRCHILD SEMICONDUCTOR RESERVES THE RIGHT TO MAKE CHANGES WITHOUT FURTHER NOTICE TO ANY PRODUCTS HEREIN TO IMPROVE RELIABILITY, FUNCTION, OR DESIGN. TO OBTAIN THE LATEST, MOST UP-TO-DATE DATASHEET AND PRODUCT INFORMATION, VISIT OUR WEBSITE AT HTTP://WWW.FAIRCHILDSEMI.COM. FAIRCHILD DOES NOT ASSUME ANY LIABILITY ARISING OUT OF THE APPLICATION OR USE OF ANY PRODUCT OR CIRCUIT DESCRIBED HEREIN; NEITHER DOES IT CONVEY ANY LICENSE UNDER ITS PATENT RIGHTS, NOR THE RIGHTS OF OTHERS. THESE SPECIFICATIONS DO NOT EXPAND THE TERMS OF FAIRCHILD'S WORLDWIDE TERMS AND CONDITIONS. SPECIFICALLY THE WARRANTY THEREIN, WHICH COVERS THESE PRODUCTS.

#### LIFE SUPPORT POLICY

FAIRCHILD'S PRODUCTS ARE NOT AUTHORIZED FOR USE AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS WITHOUT THE EXPRESS WRITTEN APPROVAL OF FAIRCHILD SEMICONDUCTOR CORPORATION.

- 1. Life support devices or systems are devices or systems which, (a) are intended for surgical implant into the body or (b) support or sustain life, and (c) whose failure to perform when properly used in accordance with instructions for use provided in the labeling, can be reasonably expected to result in a significant injury of the user.
- 2. A critical component in any component of a life support, device, or system whose failure to perform can be reasonably expected to cause the failure of the life support device or system, or to affect its safety or effectiveness.

### **ANTI-COUNTERFEITING POLICY**

Fairchild Semiconductor Corporation's Anti-Counterfeiting Policy. Fairchild's Anti-Counterfeiting Policy is also stated on our external website, www.fairchildsemi.com, under Sales Support.

Counterfeiting of semiconductor parts is a growing problem in the industry. All manufacturers of semiconductor products are experiencing counterfeiting of their parts. Customers who inadvertently purchase counterfeit parts experience many problems such as loss of brand reputation, substandard performance, failed applications, and increased cost of production and manufacturing delays. Fairchild is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. Fairchild strongly encourages customers to purchase Fairchild parts either directly from Fairchild or from Authorized Fairchild Distributors who are listed by country on our web page cited above. Products customers buy either from Fairchild directly or from Authorized Fairchild Distributors are genuine parts, have full traceability, meet Fairchild's quality standards for handling and storage and provide access to Fairchild's full range of up-to-date technical and product information. Fairchild and our Authorized Distributors will stand behind all warranties and will appropriately address any warranty issues that may arise. Fairchild will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources. Fairchild is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.

#### PRODUCT STATUS DEFINITIONS

Definition of Terms				
Datasheet Identification	Product Status	Definition		
Advance Information	Formative / In Design	Datasheet contains the design specifications for product development. Specifications may change in any manner without notice.		
Preliminary	First Production	Datasheet contains preliminary data; supplementary data will be published at a later date. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve design.		
No Identification Needed	Full Production	Datasheet contains final specifications. Fairchild Semiconductor reserves the right to make changes at any time without notice to improve the design.		
Obsolete	Not In Production	Datasheet contains specifications on a product that is discontinued by Fairchild Semiconductor. The datasheet is for reference information only.		

Rev. 172

# **Mouser Electronics**

**Authorized Distributor** 

Click to View Pricing, Inventory, Delivery & Lifecycle Information:

Fairchild Semiconductor: 1N4007 1N4001\_Q 1N4007\_Q